

Network Working Group
Request for Comments: 5601
Category: Standards Track

T. Nadeau, Ed.
BT
D. Zelig, Ed.
Oversi
July 2009

Pseudowire (PW) Management Information Base (MIB)

Abstract

This memo defines a Standards Track portion of the Management Information Base for use with network management protocols in the Internet community. In particular, it describes managed objects for modeling of Pseudowire Edge-to-Edge services carried over a general Packet Switched Network.

Status of This Memo

This document specifies an Internet standards track protocol for the Internet community, and requests discussion and suggestions for improvements. Please refer to the current edition of the "Internet Official Protocol Standards" (STD 1) for the standardization state and status of this protocol. Distribution of this memo is unlimited.

Copyright Notice

Copyright (c) 2009 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents in effect on the date of publication of this document (<http://trustee.ietf.org/license-info>). Please review these documents carefully, as they describe your rights and restrictions with respect to this document.

This document may contain material from IETF Documents or IETF Contributions published or made publicly available before November 10, 2008. The person(s) controlling the copyright in some of this material may not have granted the IETF Trust the right to allow modifications of such material outside the IETF Standards Process. Without obtaining an adequate license from the person(s) controlling the copyright in such materials, this document may not be modified outside the IETF Standards Process, and derivative works of it may not be created outside the IETF Standards Process, except to format it for publication as an RFC or to translate it into languages other than English.

Table of Contents

1. Introduction	2
2. The Internet-Standard Management Framework	2
3. Conventions	3
4. Overview	3
5. Structure of the MIB Module	3
6. PW-STD-MIB Module Usage	4
7. Relations to Other PWE3 MIB Modules	5
8. Relations to the IF-MIB	5
9. PW Notifications	6
10. Example of the PW MIB Modules Usage	6
11. IANA PWE3 MIB Module	8
12. Object Definitions	11
13. Security Considerations	62
14. IANA Considerations	63
14.1. ifType for PW	63
14.2. PW MIB Modules OBJECT IDENTIFIER Values	63
14.3. IANA Considerations for PW-STD-MIB	64
14.4. IANA Considerations for IANA-PWE3-MIB	64
15. Acknowledgments	64
16. References	64
16.1. Normative References	64
16.2. Informative References	66

1. Introduction

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it defines a MIB module that can be used to manage pseudowire (PW) services for transmission over a Packet Switched Network (PSN) [RFC3931] [RFC4447]. This MIB module provides generic management of PWs that is common to all types of PSN and PW services defined by the IETF PWE3 Working Group.

2. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to section 7 of RFC 3410 [RFC3410].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB

module that is compliant to the SMIV2, which is described in STD 58, RFC 2578 [RFC2578], STD 58, RFC 2579 [RFC2579] and STD 58, RFC 2580 [RFC2580].

3. Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [BCP14].

This document adopts the definitions, acronyms, and mechanisms described in [RFC3985] and [RFC3916]. Unless otherwise stated, the mechanisms of [RFC3985] apply and will not be re-described here.

4. Overview

The PWE3 MIB modules architecture provides a layered modular model into which any supported emulated service can be connected to any supported PSN type. This specific MIB module provides the glue for mapping between the emulated service onto the native PSN service. As such, the defining of a PW emulated service requires the use of at least three types of MIB modules.

Starting from the emulated service, the first type is a service-specific module, which is dependent on the emulated signal type. These modules are defined in other documents.

The second type is this module, the PW-STD-MIB module, which configures general parameters of the PW that are common to all types of emulated services and PSN types.

The third type of module is a PSN-specific module. There is a different module for each type of PSN. These modules associate the PW with one or more "tunnels" that carry the service over the PSN. These modules are defined in other documents.

5. Structure of the MIB Module

The MIB module consists of six tables:

- The generic configuration and status monitoring objects that are common to all service types and PSN types (pwTable).
- The PW Performance Current Table (pwPerfCurrentTable) contains PW statistics for the current 15-minute period.

- The PW Performance Interval Table (pwPerfIntervalTable) contains PW statistics for historical intervals (usually 96 15-minute entries to cover a 24-hour period).
- The PW Performance 1-day Interval Table (pwPerf1DayIntervalTable) contains PW statistics for historical intervals accumulated per day. Usually 30 1-day entries to cover a monthly period.
- The mapping table (pwIndexMappingTable) enables the reverse mapping of the unique Pwid parameters [peer IP, PW type, and PW ID] and the pwIndex.
- The mapping table (pwGenFecIndexMappingTable) enables the reverse mapping of unique Pwid parameters used in genFecSignaling [pwGroupAttachmentID, pwLocalAttachmentID, and pwPeerAttachmentID] and the pwIndex.

This MIB module uses Textual Conventions from [RFC2578], [RFC2579], [RFC2580], [RFC2863], [RFC3411], [RFC3593], [RFC3705], [RFC4001], and [RFC5542], and references [RFC3413], [RFC4623], and [RFC4720].

6. PW-STD-MIB Module Usage

An entry in the PW table (pwTable) MUST exist for all PW types (ATM, FR, Ethernet, SONET, etc.). This table holds generic parameters related to the PW creation and monitoring.

A conceptual row can be created in the pwTable in one of the following ways:

- 1) The operator creates a row in the pwTable when configuring the node for a new service. This mode MUST be supported by the agent, and MUST be used when creating a non-signaled (manually assigned) PW.
 - 2) The agent MAY create a row in the pwTable if a signaling message has been received from a peer node with signaling identification parameters that are not already known to the local node (i.e., there is no related entry created by the operator with matching parameters). This mode is OPTIONAL.
 - 3) The agent MAY create a row in the pwTable automatically due to some auto-discovery application, or based on configuration that is done through non-SNMP applications. This mode is OPTIONAL.
- The agent then creates the rows in the (locally supported) performance tables and reverse-mapping tables in PW-STD-MIB module.

7. Relations to Other PWE3 MIB Modules

- Based on the PSN type defined for the PW, a row is created in the PSN-specific module (for example, [RFC5602]) and associated to the PW table by the common pwIndex.
- Based on the PW type defined for the PW, a row is created in the service-specific module (for example, [CEPMIB]) and associated to the PW table by the common pwIndex.
- Unless all the necessary entries in the applicable tables have been created and all the parameters have been consistently configured in those tables, signaling cannot be performed from the local node, and the pwVcOperStatus should report 'notPresent'.

8. Relations to the IF-MIB

The PW in general is not an ifIndex [RFC2863] on its own, for agent scalability reasons. The PW is typically associated via the PWE3 MIB modules to an ifIndex the PW is emulating. This ifIndex may represent a physical entity -- for example, a PW emulating a SONET path as in Circuit Emulation Service over Packet (CEP). In that case, the PW itself is not an ifIndex; however, the PW-STD-CEP-MIB module associates the PW to the ifIndex of the path to be emulated. In some cases, the PW will be associated to an ifIndex representing a virtual interface. An example is Virtual Private LAN Service (VPLS) where the PW emulates a logical interface of a (logical) bridge. The physical ports' association to the VPLS instance is defined in the non-PW MIB modules in this case.

Exception to the above MAY exist in some implementations where it is convenient to manage the PW as an ifIndex in the ifTable. A special ifType to represent a PW virtual interface (246) will be used in the ifTable in this case.

When the PW is managed as an ifIndex, by default it SHOULD NOT be stacked, i.e., this ifIndex SHOULD NOT be layered above the respective PSN tunnel ifIndex or the attachment circuit ifIndex or the interface carrying the attachment circuit.

Note that the ifIndex that carries the PW toward/from the PSN is not explicitly configured via PWE3 MIB modules except in rare cases. In most cases, the PW is carried inside a PSN tunnel, and the interfaces carrying the tunnel are specified in the related MIB modules that control the PSN tunnels.

9. PW Notifications

This MIB module includes notifications for PW entering the up or down state, in accordance with the guidelines for interface notifications as described in [RFC2863]. Implementers should be aware that in many systems, it is desired to correlate notifications, such that notifications will not be emitted if notifications from a higher level (such as ports or tunnels) are already in effect. Specifically for PWs, it is anticipated that most network's equipment failures turn into lowerLayerDown state at the PW level, where a notification has already been emitted from a higher level.

When a PW is represented as an ifIndex, it is RECOMMENDED that PW notifications be turned off, to avoid duplication with the ifIndex status change notifications.

10. Example of the PW MIB Modules Usage

In this section, we provide an example of using the MIB objects described in section 7 to set up a CEP PW over Multiprotocol Label Switching (MPLS) PSN. While this example is not meant to illustrate every permutation of the MIB, it is intended as an aid to understanding some of the key concepts. It is meant to be read after going through the MIB itself.

In this example, a PW service for CEP is configured over an MPLS PSN (MPLS-TE tunnel). It uses LDP as in [RFC4447] for service setup.

For the operation in the service-specific MIB modules and the PSN-specific MIB modules, see the specific MIB module memo. This example is continued in the memo describing the PW-CEP-STD-MIB module (for example, [CEPMIB]) and the PW-MPLS-STD-MIB module [RFC5602].

In the PW-STD-MIB module:

In pwTable:

```

{
  pwIndex                5,

  pwType                 cep,
  pwOwner                pwIdFecSignaling,
  pwPsnType              mpls,
  pwSetUpPriority        0, -- Highest
  pwHoldingPriority      0, -- Highest
  pwInboundMode         loose,

  pwPeerAddrType         ipv4,
  pwPeerAddr             192.0.2.5, -- In this case, equal to the
                                -- peer LDP entity IP addr

  pwID                   10,
  pwLocalGroupID        12,
  ..

  pwCwPreference         true,  -- Actually ignored for CEP
  pwLocalIfMtu           0,    -- Do not send ifMtu parameter
  pwLocalIfString        false, -- Do not send interface string
  pwCapabAdvert          0,    -- Does not support status
                                -- report to the peer.
  pwRemoteGroupID       0xFFFF, -- Will be received by
                                -- signaling protocol

  pwRemoteCwStatus       notKnownYet,
  pwRemoteIfMtu          0,
  pwRemoteIfString       "",
  pwRemoteCapabilities   notYetKnown,
  ..
  pwOutboundVcLabel      0xFFFF, -- Will be received by
                                -- signaling protocol
  pwInboundVcLabel       0xFFFF, -- Will be set by signaling
                                -- protocol
  pwName                 "Example of CEP PW",
  pwDescr                "",
  ..

  pwAdminStatus         up,
  ..
}

```

11. IANA PWE3 MIB Module

This section contains the initial version of the IANA-PWE3-MIB. IANA has updated this MIB module based on expert review as defined in [RFC5226]. Each new assignment of PW type or PW PSN type made by IANA based on the procedures described in [RFC4446] should be documented in the online version of IANA-PWE3-MIB. The current IANA-PWE3-MIB contains PW types as requested in [RFC4446] and [RFC4863].

```
IANA-PWE3-MIB DEFINITIONS ::= BEGIN
```

```
IMPORTS
```

```
  MODULE-IDENTITY, mib-2
    FROM SNMPv2-SMI -- [RFC2578]
```

```
  TEXTUAL-CONVENTION
    FROM SNMPv2-TC; -- [RFC2579]
```

```
ianaPwe3MIB MODULE-IDENTITY
```

```
  LAST-UPDATED "200906110000Z" -- 11 June 2009 00:00:00 GMT
  ORGANIZATION "IANA"
```

```
  CONTACT-INFO
```

```
    "Internet Assigned Numbers Authority
     Internet Corporation for Assigned Names and Numbers
     4676 Admiralty Way, Suite 330
     Marina del Rey, CA 90292-6601
```

```
    Phone: +1 310 823 9358
```

```
    EMail: iana@iana.org"
```

```
  DESCRIPTION
```

```
    "This MIB module defines the IANAPwTypeTC and
     IANAPwPsnTypeTC textual conventions for use in PWE3
     MIB modules.
```

```
    Any additions or changes to the contents of this MIB
     module require either publication of an RFC, Designated
     Expert Review as defined in RFC 5226, Guidelines for
     Writing an IANA Considerations Section in RFCs, and should
     be based on the procedures defined in [RFC4446]. The
     Designated Expert will be selected by the IESG Area
     Director(s) of the internet Area.
```

```
    Copyright (c) 2009 IETF Trust and the persons identified as
     authors of the code. All rights reserved.
```

```
    Redistribution and use in source and binary forms, with or
     without modification, are permitted provided that the
```


following conditions are met:

- Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- Neither the name of Internet Society, IETF or IETF Trust, nor the names of specific contributors, may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS 'AS IS' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE. "

```
REVISION      "200906110000Z"  -- 11 June 2009 00:00:00 GMT
DESCRIPTION   "Original version, published as part of RFC 5601."
 ::= { mib-2 174 }
```

```
IANAPwTypeTC ::= TEXTUAL-CONVENTION
  STATUS      current
  DESCRIPTION
    "Indicates the PW type (i.e., the carried service). "
  SYNTAX      INTEGER {
    other(0),
    frameRelayDlciMartiniMode(1),
    atmAal5SduVcc(2),
    atmTransparent(3),
    ethernetTagged(4),
    ethernet(5),
    hdlc(6),
    ppp(7),
```

```

cem(8), -- Historic type
atmCellNtolVcc(9),
atmCellNtolVpc(10),
ipLayer2Transport(11),
atmCell1tolVcc(12),
atmCell1tolVpc(13),
atmAal5PduVcc(14),
frameRelayPortMode(15),
cep(16),
e1Satop(17),
t1Satop(18),
e3Satop(19),
t3Satop(20),
basicCesPsn(21),
basicTdmIp(22),
tdmCasCesPsn(23),
tdmCasTdmIp(24),
frDlci(25),
wildcard (32767)
}

```

IANAPwPsnTypeTC ::= TEXTUAL-CONVENTION

STATUS current

DESCRIPTION

"Identifies the PSN type that the PW will use over the network."

```

SYNTAX INTEGER {
    mpls          (1),
    l2tp          (2),
    udpOverIp    (3),
    mplsOverIp   (4),
    mplsOverGre  (5),
    other        (6)
}

```

IANAPwCapabilities ::= TEXTUAL-CONVENTION

STATUS current

DESCRIPTION

"This TC describes a collection of capabilities related to a specific PW.

Values may be added in the future based on new capabilities introduced in IETF documents.

"

```

SYNTAX BITS {
    pwStatusIndication (0), -- Applicable only if maintenance
                           -- protocol is in use.
    pwVCCV              (1)
}

```

END

12. Object Definitions

PW-STD-MIB DEFINITIONS ::= BEGIN

IMPORTS

NOTIFICATION-TYPE, MODULE-IDENTITY, OBJECT-TYPE,
Integer32, Unsigned32, Counter32, Counter64, TimeTicks,
transmission

FROM SNMPv2-SMI -- [RFC2578]

MODULE-COMPLIANCE, OBJECT-GROUP, NOTIFICATION-GROUP
FROM SNMPv2-CONF -- [RFC2580]

TruthValue, RowStatus, StorageType,
TimeStamp
FROM SNMPv2-TC -- [RFC2579]

SnmpAdminString
FROM SNMP-FRAMEWORK-MIB -- [RFC3411]

InterfaceIndexOrZero
FROM IF-MIB -- [RFC2863]

InetAddressType, InetAddress
FROM INET-ADDRESS-MIB -- [RFC4001]

PerfCurrentCount, PerfIntervalCount
FROM PerfHist-TC-MIB -- [RFC3593]

HCPperfCurrentCount, HCPperfIntervalCount, HCPperfTimeElapsed,
HCPperfValidIntervals
FROM HC-PerfHist-TC-MIB -- [RFC3705]

PwIndexType, PwIndexOrZeroType, PwGroupID, PwIDType,
PwOperStatusTC, PwAttachmentIdentifierType, PwCwStatusTC,
PwStatus, PwFragSize, PwFragStatus, PwGenIdType
FROM PW-TC-STD-MIB -- [RFC5542]
IANAPwTypeTC, IANAPwPsnTypeTC, IANAPwCapabilities
FROM IANA-PWE3-MIB -- [RFC5601]

;

pwStdMIB MODULE-IDENTITY

LAST-UPDATED "200906110000Z" -- 11 June 2009 00:00:00 GMT

ORGANIZATION "Pseudowire Edge-to-Edge Emulation (PWE3) Working
Group"

CONTACT-INFO

"David Zelig
Email: davidz@oversi.com

Thomas D. Nadeau
Email: tom.nadeau@bt.com

The PWE3 Working Group (email distribution pwe3@ietf.org,
<http://www.ietf.org/html.charters/pwe3-charter.html>)

"

DESCRIPTION

"This MIB module contains managed object definitions for pseudowire operation as in Bryant, S. and P. Pate, 'Pseudo Wire Emulation Edge-to-Edge (PWE3) Architecture' [RFC3985], Martini, L., et al, 'Pseudowire Setup and Maintenance Using the Label Distribution Protocol (LDP)' [RFC4447], and Townsley, M., et al, 'Layer Two Tunneling Protocol (Version 3)' [RFC3931].

This MIB module enables the use of any underlying packet switched network (PSN). MIB nodules that will support PW operations over specific PSN types are defined in separate memos.

The indexes for this MIB module are also used to index the PSN-specific tables and the PW-specific tables. The PW Type dictates which PW-specific MIB module to use.

Copyright (c) 2009 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- Neither the name of Internet Society, IETF or IETF Trust, nor the names of specific contributors, may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS 'AS IS' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

This version of this MIB module is part of RFC 5601;
see the RFC itself for full legal notices.

"

-- Revision history.

REVISION

"200906110000Z" -- 11 June 2009 00:00:00 GMT

DESCRIPTION "Initial version published as part of RFC 5601."

::= { transmission 246 }

-- Top-level components of this MIB.

-- Notifications

pwNotifications OBJECT IDENTIFIER

::= { pwStdMIB 0 }

-- Tables, Scalars

pwObjects OBJECT IDENTIFIER

::= { pwStdMIB 1 }

-- Conformance

pwConformance OBJECT IDENTIFIER

::= { pwStdMIB 2 }

-- PW Virtual Connection Table

pwIndexNext OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This object contains an appropriate value to be used for pwIndex when creating entries in the pwTable. The value 0 indicates that no unassigned entries are available. To obtain the value of pwIndex for a new entry in the pwTable,

the manager issues a management protocol retrieval operation. The agent will determine through its local policy when this index value will be made available for reuse."

::= { pwObjects 1 }

pwTable OBJECT-TYPE

SYNTAX SEQUENCE OF PwEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table specifies information for configuring and status monitoring that is common to all service types and PSN types."

::= { pwObjects 2 }

pwEntry OBJECT-TYPE

SYNTAX PwEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"A row in this table represents a pseudowire (PW) virtual connection across a packet network. It is indexed by pwIndex, which uniquely identifies a singular connection.

A row can be created by an operator command from a management plan of a PE, by signaling, or due to auto-discovery process. An operator's command can be issued via a non-SNMP application; in such case, a row will be created implicitly by the agent.

The read-create objects in this table are divided into three categories:

- 1) Objects that MUST NOT be changed after row activation. These are objects that define basic properties of the PW (for example type, destination, etc.).
- 2) Objects that MAY be changed when the PW is defined as not active. A change of these objects involves re-signaling of the PW or it might be traffic affecting. PW not active is defined as one of the following conditions:
 - a) The pwRowStatus is notInService(2).
 - b) The pwRowStatus is notReady(3).
 - c) The pwAdminStatus is down(2).

If the operator needs to change one of the values for an active row, the operator can either set the pwRowStatus to notInService(2) or set pwAdminStatus to down(2).

Signaling (or traffic) is initiated again upon setting the pwRowStatus to active(1) or setting the pwAdminStatus to up(1) or testing(3), respectively.

3) Objects that MAY be changed at any time.

A PW MAY have an entry in the ifTable in addition to the entry in this table. In this case, a special ifType for PW will be set in the ifTable, and the ifIndex in the ifTable of the PW will be set in the pwIfIndex object in this table.

By default, all the read-create objects MUST NOT be changed after row activation, unless specifically indicated in the individual object description.

Manual entries in this table SHOULD be preserved after a reboot; the agent MUST ensure the integrity of those entries. If the set of entries of a specific row are found to be inconsistent after reboot, the PW pwOperStatus MUST be declared as notPresent(5).

```

"
INDEX { pwIndex }

 ::= { pwTable 1 }

PwEntry ::= SEQUENCE {
    pwIndex                PwIndexType,
    pwType                 IANAPwTypeTC,
    pwOwner                INTEGER,
    pwPsnType              IANAPwPsnTypeTC,
    pwSetUpPriority        Integer32,
    pwHoldingPriority      Integer32,
    pwPeerAddrType        InetAddressType,
    pwPeerAddr             InetAddress,
    pwAttachedPwIndex     PwIndexOrZeroType,
    pwIfIndex              InterfaceIndexOrZero,

    pwID                   PwIDType,
    pwLocalGroupID         PwGroupID,
    pwGroupAttachmentID   PwAttachmentIdentifierType,
    pwLocalAttachmentID   PwAttachmentIdentifierType,
    pwRemoteAttachmentID  PwAttachmentIdentifierType,

    pwCwPreference        TruthValue,
    pwLocalIfMtu           Unsigned32,

    pwLocalIfString       TruthValue,
    pwLocalCapabAdvert    IANAPwCapabilities,
    pwRemoteGroupID       PwGroupID,
    pwCwStatus             PwCwStatusTC,
    pwRemoteIfMtu         Unsigned32,

```

```

pwRemoteIfString      SnmpAdminString,
pwRemoteCapabilities  IANAPwCapabilities,

pwFragmentCfgSize     PwFragSize,
pwRmtFragCapability    PwFragStatus,
pwFcsRetentionCfg     INTEGER,
pwFcsRetentionStatus  BITS,

pwOutboundLabel       Unsigned32,
pwInboundLabel        Unsigned32,

pwName                SnmpAdminString,
pwDescr               SnmpAdminString,
pwCreateTime          TimeStamp,
pwUpTime              TimeTicks,
pwLastChange          TimeTicks,
pwAdminStatus         INTEGER,
pwOperStatus          PwOperStatusTC,
pwLocalStatus         PwStatus,
pwRemoteStatusCapable INTEGER,
pwRemoteStatus        PwStatus,
pwTimeElapsed         HCPerfTimeElapsed,
pwValidIntervals      HCPerfValidIntervals,
pwRowStatus           RowStatus,
pwStorageType         StorageType,
pwOamEnable           TruthValue,
pwGenAGIType          PwGenIdType,
pwGenLocalAllIType    PwGenIdType,
pwGenRemoteAllIType   PwGenIdType
}

```

pwIndex OBJECT-TYPE

```

SYNTAX      PwIndexType
MAX-ACCESS  not-accessible
STATUS      current

```

DESCRIPTION

"A unique index for the conceptual row identifying a PW within this table."

```
::= { pwEntry 1 }
```

pwType OBJECT-TYPE

```

SYNTAX      IANAPwTypeTC
MAX-ACCESS  read-create
STATUS      current

```

DESCRIPTION

"This value indicates the emulated service to be carried over this PW."

"


```

 ::= { pwEntry 2 }

pwOwner OBJECT-TYPE
  SYNTAX      INTEGER {
    manual          (1),
    pwIdFecSignaling (2), -- PW signaling with PW ID FEC
    genFecSignaling (3), -- Generalized attachment FEC
    l2tpControlProtocol (4),
    other           (5)
  }
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
    "This object is set by the operator to indicate the protocol
    responsible for establishing this PW.
    'manual' is used in all cases where no maintenance
    protocol (PW signaling) is used to set up the PW, i.e.,
    configuration of entries in the PW tables including
    PW labels, etc., is done by setting the MIB fields manually.
    'pwIdFecSignaling' is used in case of signaling with the
    Pwid FEC element with LDP signaling.
    'genFecSignaling' is used in case of LDP signaling with
    the generalized FEC.
    'l2tpControlProtocol' indicates the use of the L2TP
    control protocol.
    'other' is used for other types of signaling."
 ::= { pwEntry 3 }

pwPsnType OBJECT-TYPE
  SYNTAX      IANAPwPsnTypeTC
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
    "This object is set by the operator to indicate the PSN type.
    Based on this object, the relevant PSN table's entry is
    created in the PSN-specific MIB modules.
    "
 ::= { pwEntry 4 }

pwSetUpPriority OBJECT-TYPE
  SYNTAX      Integer32 (0..7)
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
    "This object defines the relative priority of the PW
    during set-up in a lowest-to-highest fashion, where 0
    is the highest priority. PWs with the same priority
    are treated with equal priority. PWs that have not yet

```

completed setup will report 'dormant' in the pwOperStatus.

This value is significant if there are competing resources among PWs and the implementation supports this feature. Equal priority handling with competing resources is implementation specific.

This object MAY be changed at any time."

```
DEFVAL { 0 }
 ::= { pwEntry 5 }
```

pwHoldingPriority OBJECT-TYPE

SYNTAX Integer32 (0..7)

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"This object defines the relative holding priority of the PW in a lowest-to-highest fashion, where 0 is the highest priority. PWs with the same priority are treated equally. This value is significant if there are competing resources among PWs and the implementation supports this feature. Equal priority handling with competing resources is implementation specific.

This object MAY be changed only if the PW is not active."

```
DEFVAL { 0 }
 ::= { pwEntry 6 }
```

pwPeerAddrType OBJECT-TYPE

SYNTAX InetAddressType

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"Denotes the address type of the peer node. It should be set to 'unknown' if PE/PW maintenance protocol is not used and the address is unknown."

```
DEFVAL { ipv4 }
 ::= { pwEntry 8 }
```

pwPeerAddr OBJECT-TYPE

SYNTAX InetAddress

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"This object contains the value of the peer node address of the PW/PE maintenance protocol entity. This object SHOULD contain a value of all zeroes if not applicable (pwPeerAddrType is 'unknown')."

```
 ::= { pwEntry 9 }
```

```
pwAttachedPwIndex OBJECT-TYPE
    SYNTAX          PwIndexOrZeroType
    MAX-ACCESS      read-create
    STATUS          current
    DESCRIPTION
        "If the PW is attached to another PW instead of a local
        native service, this item indicates the pwIndex of the
        attached PW.  Otherwise, this object MUST
        be set to zero.  Attachment to another PW will have no
        PW specific entry in any of the service MIB modules."
    DEFVAL { 0 }
    ::= { pwEntry 10 }

pwIfIndex OBJECT-TYPE
    SYNTAX          InterfaceIndexOrZero
    MAX-ACCESS      read-create
    STATUS          current
    DESCRIPTION
        "This object indicates the ifIndex of the PW if the PW is
        represented in the ifTable.  Otherwise, it MUST be set
        to zero."
    DEFVAL { 0 }
    ::= { pwEntry 11 }

pwID OBJECT-TYPE
    SYNTAX          PwIDType
    MAX-ACCESS      read-create
    STATUS          current
    DESCRIPTION
        "Pseudowire identifier.

        If the pwOwner object is 'pwIdFecSignaling' or
        'l2tpControlProtocol', then this object is signaled in the
        outgoing PW ID field within the 'Virtual Circuit FEC
        Element'.  For other values of pwOwner, this object is not
        signaled and it MAY be set to zero.

        For implementations that support the pwIndexMappingTable,
        a non-zero value is RECOMMENDED, even if this
        identifier is not signaled.  This is so that reverse
        mappings can be provided by pwIndexMappingTable and
        pwPeerMappingTable.  It is therefore RECOMMENDED that the
        value of this pwID be unique (or if pwPeerAddrType is not
        'unknown', at least [pwType, pwID, pwPeerAddrType, pwPeerAddr]
        is unique.)"
    REFERENCE
        "Martini, et al, 'Pseudowire Setup and Maintenance using
        the Label Distribution Protocol', RFC 4447."
```

```
 ::= { pwEntry 12 }

pwLocalGroupID OBJECT-TYPE
    SYNTAX      PwGroupID
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Used in the Group ID field sent to the peer PW End Service
        within the maintenance protocol used for PW setup.
        It SHOULD be set to zero if a maintenance protocol is
        not used."
    REFERENCE
        "Martini, et al, 'Pseudowire Setup and Maintenance using
        the Label Distribution Protocol', RFC 4447."
 ::= { pwEntry 13 }

pwGroupAttachmentID OBJECT-TYPE
    SYNTAX      PwAttachmentIdentifierType
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "This object is an octet string representing the attachment
        group identifier (AGI) that this PW belongs to, which
        typically identifies the VPN ID.
        Applicable if pwOwner equals 'genFecSignaling'."
    REFERENCE
        "Martini, et al, 'Pseudowire Setup and Maintenance using
        the Label Distribution Protocol', RFC 4447."
 ::= { pwEntry 14 }

pwLocalAttachmentID OBJECT-TYPE
    SYNTAX      PwAttachmentIdentifierType
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "This object is an octet string representing the local
        forwarder attachment individual identifier (AII) to be
        used by this PW. It is used as the Source AII (SAII) for
        outgoing signaling messages and the Target AII (TAII) in
        the incoming messages from the peer. Applicable if
        pwOwner equal 'genFecSignaling'."
    REFERENCE
        "Martini, et al, 'Pseudowire Setup and Maintenance using
        the Label Distribution Protocol', RFC 4447."
 ::= { pwEntry 15 }
```

```
pwRemoteAttachmentID OBJECT-TYPE
    SYNTAX      PwAttachmentIdentifierType
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "This object is an octet string representing the remote
        forwarder attachment individual identifier (AII) to be
        used by this PW. It is used as the TAI for outgoing
        signaling messages and the SAI in the incoming messages
        from the peer.
        Applicable if pwOwner equals 'genFecSignaling'."
    REFERENCE
        "Martini, et al, 'Pseudowire Setup and Maintenance using
        the Label Distribution Protocol', RFC 4447."
    ::= { pwEntry 16 }

pwCwPreference OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Defines if the control word will be sent with each packet
        by the local node. Some PW types mandate the use of a
        control word, and in such cases, the value configured for
        this object has no effect on the existence of the control
        word.
        This object MAY be changed only if the PW is not active."
    REFERENCE
        "Martini, et al, 'Pseudowire Setup and Maintenance using
        the Label Distribution Protocol.', RFC 4447."
    DEFVAL { false }
    ::= { pwEntry 17 }

pwLocalIfMtu OBJECT-TYPE
    SYNTAX      Unsigned32 (0..65535)
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "If not equal to zero, the optional IfMtu object in the
        signaling protocol will be sent with this value, which
        represents the locally supported MTU size over the
        interface (or the virtual interface) associated with the
        PW.
        This object MAY be changed only if the PW is not active."
    REFERENCE
        "Martini, et al, 'Pseudowire Setup and Maintenance using
        the Label Distribution Protocol', RFC 4447."
    DEFVAL { 0 }
```

```
::= { pwEntry 18 }
```

pwLocalIfString OBJECT-TYPE
SYNTAX TruthValue
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"A PW MAY be associated to an interface (or a virtual interface) in the ifTable of the node as part of the service configuration. This object defines if the maintenance protocol will send the interface's name (ifAlias) as it appears in the ifTable. If set to false, the optional element will not be sent. This object MAY be changed only if the PW is not active."
REFERENCE
"Martini, et al, 'Pseudowire Setup and Maintenance using the Label Distribution Protocol', RFC 4447, section 5.5."
DEFVAL { false }
::= { pwEntry 19 }

pwLocalCapabAdvert OBJECT-TYPE
SYNTAX IANAPwCapabilities
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"If a maintenance protocol is used, it indicates the capabilities the local node will advertise to the peer. The operator MAY selectively assign a partial set of capabilities. In case of manual configuration of the PW, the operator SHOULD set non-conflicting options (for example, only a single type of Operations, Administration, and Management (OAM)) out of the available options in the implementation. It is possible to change the value of this object when the PW is not active. The agent MUST reject any attempt to set a capability that is not supported.

The default value MUST be the full set of local node capabilities."
REFERENCE
"Martini, et al, 'Pseudowire Setup and Maintenance using the Label Distribution Protocol', RFC 4447."
::= { pwEntry 20 }

pwRemoteGroupID OBJECT-TYPE
SYNTAX PwGroupID
MAX-ACCESS read-only
STATUS current

DESCRIPTION

"This object is obtained from the Group ID field as received via the maintenance protocol used for PW setup. Value of zero will be reported if not used. Value of 0xFFFFFFFF shall be used if the object is yet to be defined by the PW maintenance protocol."

REFERENCE

"Martini, et al, 'Pseudowire Setup and Maintenance using the Label Distribution Protocol', RFC 4447."

::= { pwEntry 21 }

pwCwStatus OBJECT-TYPE

SYNTAX PwCwStatusTC
MAX-ACCESS read-only
STATUS current

DESCRIPTION

"If signaling is used for PW establishment, this object indicates the status of the control word negotiation. For either signaling or manual configuration, it indicates if the control word (CW) is to be present for this PW."

REFERENCE

"Martini, et al, 'Pseudowire Setup and Maintenance using the Label Distribution Protocol', RFC 4447."

::= { pwEntry 22 }

pwRemoteIfMtu OBJECT-TYPE

SYNTAX Unsigned32
MAX-ACCESS read-only
STATUS current

DESCRIPTION

"The remote interface MTU as (optionally) received from the remote node via the maintenance protocol. The object SHOULD report zero if the MTU is not available."

REFERENCE

"Martini, et al, 'Pseudowire Setup and Maintenance using the Label Distribution Protocol', RFC 4447."

::= { pwEntry 23 }

pwRemoteIfString OBJECT-TYPE

SYNTAX SnmpAdminString (SIZE (0..80))
MAX-ACCESS read-only
STATUS current

DESCRIPTION

"Indicates the interface description string as received by the maintenance protocol. It MUST be a NULL string if a maintenance protocol is not used or the value is not known yet."

REFERENCE

"Martini, et al, 'Pseudowire Setup and Maintenance using the Label Distribution Protocol', RFC 4447, section 5.5."
 ::= { pwEntry 24 }

pwRemoteCapabilities OBJECT-TYPE

SYNTAX IANAPwCapabilities
 MAX-ACCESS read-only
 STATUS current

DESCRIPTION

"Indicates the capabilities as received from the peer."

REFERENCE

"Martini, et al, 'Pseudowire Setup and Maintenance using the Label Distribution Protocol', RFC 4447."
 ::= { pwEntry 25 }

pwFragmentCfgSize OBJECT-TYPE

SYNTAX PwFragSize
 UNITS "bytes"
 MAX-ACCESS read-create
 STATUS current

DESCRIPTION

"If set to a value other than zero, indicates that fragmentation is desired for this PW.
 This object MAY be changed only if the PW is not active."

REFERENCE

"Malis A., Townsley M., 'PWE3 Fragmentation and Reassembly', RFC 4623."
 DEFVAL { 0 } -- i.e., fragmentation not desired
 ::= { pwEntry 26 }

pwRmtFragCapability OBJECT-TYPE

SYNTAX PwFragStatus
 MAX-ACCESS read-only
 STATUS current

DESCRIPTION

"The status of the fragmentation based on the local configuration and the peer capabilities as received from the peer when a control protocol is used."

REFERENCE

"Malis A., Townsley M., 'PWE3 Fragmentation and Reassembly', RFC 4623."
 ::= { pwEntry 27 }

pwFcsRetentionCfg OBJECT-TYPE

SYNTAX INTEGER {
 fcsRetentionDisable (1),
 fcsRetentionEnable (2)


```

}
MAX-ACCESS      read-create
STATUS          current
DESCRIPTION
    "The local configuration of Frame Check Sequence (FCS)
    retention for this PW. FCS retention can be configured for
    PW types High-Level Data Link Control (HDLC), Point-to-Point
    Protocol (PPP), and Ethernet only. If the implementation
    does not support FCS retention, an error MUST be reported in
    pwFcsRetentionStatus. This object MAY be changed only if
    the PW is not active."
REFERENCE
    "Malis A., et al., 'PWE3 Frame Check Sequence Retention',
    RFC 4720."
DEFVAL { fcsRetentionDisable }
 ::= { pwEntry 28 }

```

pwFcsRetentionStatus OBJECT-TYPE

```

SYNTAX      BITS {
    remoteIndicationUnknown      (0),
    remoteRequestFcsRetention    (1),
    fcsRetentionEnabled          (2),
    fcsRetentionDisabled         (3),
    localFcsRetentionCfgErr      (4),
    fcsRetentionFcsSizeMismatch (5)
}

```

```
MAX-ACCESS      read-only
```

```
STATUS          current
```

DESCRIPTION

"The status of the FCS retention negotiation process based on local configuration and the remote advertisement.

remoteIndicationUnknown - set if a FEC has not been received from the remote.

remoteRequestFcsRetention - indicates that the peer has requested FCS retention. FCS retention will be used if the local node is capable and configured to use it for this PW.

fcsRetentionEnabled - FCS retention is enabled (both peers were configured for FCS retention for signaled PW, or the local node is configured and capable of FCS retention for manually assigned PWs).

fcsRetentionDisabled - FCS retention is disabled (not configured locally or not advertised by the peer).

localFcsRetentionCfgErr - set if the local node has been configured for FCS retention but is not capable to support it.

fcsRetentionFcsSizeMismatch - set if there is an FCS size mismatch between the local and the peer node.

"

REFERENCE

"Malis A., et al., 'PWE3 Frame Check Sequence Retention', RFC 4720"

::= { pwEntry 29 }

pwOutboundLabel OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The PW label used in the outbound direction (i.e., toward the PSN). It might be set manually if pwOwner is 'manual'; otherwise, it is set automatically.

For MPLS, MPLS over IP, or MPLS over Generic Routing Encapsulation (GRE) PSN, it represents the 20-bit PW tag; for L2TP, it represents the 32-bit Session ID; and for IP PSN, it represents the destination UDP port number. If the label is not yet known (signaling in process), the object SHOULD return a value of 0xFFFFFFFF.

For manual configuration, this object MAY be changed only if the PW is not active."

::= { pwEntry 30 }

pwInboundLabel OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The PW label used in the inbound direction (i.e., packets received from the PSN). It may be set manually if pwOwner is 'manual'; otherwise, it is set automatically.

For MPLS, MPLS over IP, or MPLS over GRE PSN, it represents the 20-bit PW tag; for L2TP, it represents the 32-bit Session ID; and for IP PSN, it represents the source UDP port number.

If the label is not yet known (signaling in process), the object SHOULD return a value of 0xFFFFFFFF.

For manual configuration, this object MAY be changed only if the PW is not active."

::= { pwEntry 31 }

```
pwName OBJECT-TYPE
    SYNTAX      SnmpAdminString
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The canonical name assigned to the PW.  This object MAY be
        changed at any time."
    ::= { pwEntry 32 }

pwDescr OBJECT-TYPE
    SYNTAX      SnmpAdminString
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "A textual string containing information about the PW.
        If there is no description, this object contains a zero-
        length string.  This object MAY be changed at any time."
    ::= { pwEntry 33 }

pwCreateTime OBJECT-TYPE
    SYNTAX      TimeStamp
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The value of sysUpTime at the time this PW was created."
    ::= { pwEntry 34 }

pwUpTime OBJECT-TYPE
    SYNTAX      TimeTicks
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Specifies the time since last change of pwOperStatus to
        Up(1)."
    ::= { pwEntry 35 }

pwLastChange OBJECT-TYPE
    SYNTAX      TimeTicks
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The value of sysUpTime at the time the PW entered
        its current operational state.  If the current state was
        entered prior to the last re-initialization of the local
        network management subsystem, then this object contains a
        zero value."
    ::= { pwEntry 36 }
```

```

pwAdminStatus OBJECT-TYPE
    SYNTAX      INTEGER {
        up(1),      -- ready to pass packets
        down(2),
        testing(3) -- in a test mode
    }
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
        "The desired operational status of this PW.  This object MAY
        be set at any time."
    ::= { pwEntry 37 }

```

```

pwOperStatus OBJECT-TYPE
    SYNTAX      PwOperStatusTC
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "This object indicates the operational status of the PW; it
        does not reflect the status of the Customer Edge (CE) bound
        interface.  It is set to down only if pwNotForwarding,
        psnFacingPwRxFault, or psnFacingPwTxFault indications are
        set in pwLocalStatus or pwRemoteStatus.
        It indicates 'lowerLayerDown' if the only reason for
        not being in the 'up' state is that either the outer tunnel
        or physical layer of the network side is in the 'down'
        state.
        All other states are declared based on the description
        of the PwOperStatusTC.
        "
    ::= { pwEntry 38 }

```

```

pwLocalStatus OBJECT-TYPE
    SYNTAX      PwStatus
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "Indicates the status of the PW in the local node.
        The various indications in this object SHOULD be
        available independent of the ability of the local node to
        advertise them or the remote node to accept these status
        indications through the control protocol.
        "
    ::= { pwEntry 39 }

```

```

pwRemoteStatusCapable OBJECT-TYPE
    SYNTAX      INTEGER {
        notApplicable (1),

```

```

        notYetKnown      (2),
        remoteCapable    (3),
        remoteNotCapable (4)
    }
MAX-ACCESS      read-only
STATUS          current
DESCRIPTION
    "Indicates the remote node capability to advertise the
    PW status notification.
    notApplicable SHOULD be reported for a manually set PW, or
    if the local node is not capable of accepting the status
    notification object.
    notYetKnown SHOULD be reported if the signaling protocol
    has not yet finished the process of capability
    determination.
    remoteCapable and remoteNotcapable SHOULD be reported
    based on the initial signaling exchange that has
    determined the remote node capability.
    "
 ::= { pwEntry 40 }

pwRemoteStatus OBJECT-TYPE
    SYNTAX      PwStatus
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Indicates the status of the PW as was advertised by the
        remote.  If the remote is not capable of advertising the
        status object, or the local node is not able to accept
        the status object through signaling, then the applicable
        bit is 'pwNotForwarding', which is set if the remote has
        sent label release or label withdraw for this PW.
        "
 ::= { pwEntry 41 }

pwTimeElapsed OBJECT-TYPE
    SYNTAX      HCPerfTimeElapsed
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of seconds, including partial seconds,
        that have elapsed since the beginning of the current
        interval measurement period."
 ::= { pwEntry 42 }

pwValidIntervals OBJECT-TYPE
    SYNTAX      HCPerfValidIntervals
    MAX-ACCESS  read-only

```

```
STATUS current
DESCRIPTION
  "The number of previous 15-minute intervals
  for which data was collected."
 ::= { pwEntry 43 }

pwRowStatus OBJECT-TYPE
SYNTAX RowStatus
MAX-ACCESS read-create
STATUS current
DESCRIPTION
  "For creating, modifying, and deleting this row.
  This object MAY be changed at any time."
 ::= { pwEntry 44 }

pwStorageType OBJECT-TYPE
SYNTAX StorageType
MAX-ACCESS read-create
STATUS current
DESCRIPTION
  "This variable indicates the storage type for this
  object."
DEFVAL { nonVolatile }
 ::= { pwEntry 45 }

pwOamEnable OBJECT-TYPE
SYNTAX TruthValue
MAX-ACCESS read-create
STATUS current
DESCRIPTION
  "This variable indicates if OAM is enabled for this
  PW. It MAY be changed at any time."
DEFVAL { true }
 ::= { pwEntry 46 }

pwGenAGIType OBJECT-TYPE
SYNTAX PwGenIdType
MAX-ACCESS read-create
STATUS current
DESCRIPTION
  "This variable indicates the AGI type if generalized FEC
  (129) is used for PW signaling or configuration. It SHOULD
  return the value of zero otherwise."
DEFVAL { 0 }
 ::= { pwEntry 47 }

pwGenLocalAllIType OBJECT-TYPE
SYNTAX PwGenIdType
```

```

MAX-ACCESS      read-create
STATUS          current
DESCRIPTION
    "This object is the type of the local forwarder
    attachment individual identifier (AII) to be used
    by this PW if generalized FEC (129) is used for PW
    signaling or configuration."
DEFVAL { 0 }
 ::= { pwEntry 48 }

pwGenRemoteAIIType OBJECT-TYPE
SYNTAX          PwGenIdType
MAX-ACCESS      read-create
STATUS          current
DESCRIPTION
    "This object is the type of the remote forwarder
    attachment individual identifier (AII) to be used
    by this PW if generalized FEC (129) is used for PW
    signaling or configuration."
DEFVAL { 0 }
 ::= { pwEntry 49 }

-- End of the PW Virtual Connection Table

-- PW Performance Table

pwPerfCurrentTable OBJECT-TYPE
SYNTAX          SEQUENCE OF PwPerfCurrentEntry
MAX-ACCESS      not-accessible
STATUS          current
DESCRIPTION
    "This table provides per-PW performance information for
    the current interval."
 ::= { pwObjects 3 }

pwPerfCurrentEntry OBJECT-TYPE
SYNTAX          PwPerfCurrentEntry
MAX-ACCESS      not-accessible
STATUS          current
DESCRIPTION
    "An entry in this table is created by the agent for
    every PW."
INDEX          { pwIndex }
 ::= { pwPerfCurrentTable 1 }

PwPerfCurrentEntry ::= SEQUENCE {
    pwPerfCurrentInHCPackets      HCPerfCurrentCount,
    pwPerfCurrentInHCBytes       HCPerfCurrentCount,

```

```

pwPerfCurrentOutHCPackets      HCPerfCurrentCount,
pwPerfCurrentOutHCBytes       HCPerfCurrentCount,
pwPerfCurrentInPackets        PerfCurrentCount,
pwPerfCurrentInBytes          PerfCurrentCount,
pwPerfCurrentOutPackets       PerfCurrentCount,
pwPerfCurrentOutBytes         PerfCurrentCount
}

```

pwPerfCurrentInHCPackets OBJECT-TYPE

SYNTAX HCPerfCurrentCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"High-capacity counter for number of packets received by the PW (from the PSN) in the current 15-minute interval. This is the 64-bit version of pwPerfCurrentInPackets, if pwPerfCurrentInHCPackets is supported according to the rules spelled out in RFC 2863."

::= { pwPerfCurrentEntry 1 }

pwPerfCurrentInHCBytes OBJECT-TYPE

SYNTAX HCPerfCurrentCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"High-capacity counter for number of bytes received by the PW (from the PSN) in the current 15-minute interval. This is the 64-bit version of pwPerfCurrentInBytes, if pwPerfCurrentInHCBytes is supported according to the rules spelled out in RFC 2863."

::= { pwPerfCurrentEntry 2 }

pwPerfCurrentOutHCPackets OBJECT-TYPE

SYNTAX HCPerfCurrentCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"High-capacity counter for number of packets forwarded by the PW (to the PSN) in the current 15-minute interval. This is the 64-bit version of pwPerfCurrentOutPackets, if pwPerfCurrentOutHCPackets is supported according to the rules spelled out in RFC 2863."

::= { pwPerfCurrentEntry 3 }

pwPerfCurrentOutHCBytes OBJECT-TYPE

SYNTAX HCPerfCurrentCount

MAX-ACCESS read-only


```
STATUS          current
DESCRIPTION
    "High-capacity counter for number of bytes forwarded by
    the PW (to the PSN) in the current 15-minute interval.
    This is the 64-bit version of pwPerfCurrentOutBytes,
    if pwPerfCurrentOutHCBytes is supported according to
    the rules spelled out in RFC 2863."
 ::= { pwPerfCurrentEntry 4 }

pwPerfCurrentInPackets OBJECT-TYPE
SYNTAX          PerfCurrentCount
MAX-ACCESS      read-only
STATUS          current
DESCRIPTION
    "The counter for number of packets received by the PW (from
    the PSN) in the current 15-minute interval.
    This is the 32-bit version of pwPerfCurrentInHCPackets,
    if pwPerfCurrentInHCPackets is supported according to
    the rules spelled out in RFC 2863."
 ::= { pwPerfCurrentEntry 5 }

pwPerfCurrentInBytes OBJECT-TYPE
SYNTAX          PerfCurrentCount
MAX-ACCESS      read-only
STATUS          current
DESCRIPTION
    "The counter for number of bytes received by the
    PW (from the PSN) in the current 15-minute interval.
    It MUST be equal to the least significant 32 bits of
    pwPerfCurrentInHCBytes, if pwPerfCurrentInHCBytes is
    supported according to the rules spelled out in RFC 2863."
 ::= { pwPerfCurrentEntry 6 }

pwPerfCurrentOutPackets OBJECT-TYPE
SYNTAX          PerfCurrentCount
MAX-ACCESS      read-only
STATUS          current
DESCRIPTION
    "The counter for number of packets forwarded by
    the PW (to the PSN) in the current 15-minute interval.
    It MUST be equal to the least significant 32 bits of
    pwPerfCurrentOutHCPackets, if
    pwPerfCurrentOutHCPackets is supported according to the
    rules spelled out in RFC 2863."
 ::= { pwPerfCurrentEntry 7 }

pwPerfCurrentOutBytes OBJECT-TYPE
SYNTAX          PerfCurrentCount
```

```

MAX-ACCESS      read-only
STATUS          current
DESCRIPTION
    "The counter for number of bytes forwarded by
    the PW (to the PSN) in the current 15-minute interval.
    It MUST be equal to the least significant 32 bits of
    pwPerfCurrentOutHCBytes, if pwPerfCurrentOutHCBytes is
    supported according to the rules spelled out in RFC 2863."
 ::= { pwPerfCurrentEntry 8 }

-- End of the PW Performance Current Table

-- PW Performance Interval Table

pwPerfIntervalTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF PwPerfIntervalEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table provides per-PW performance information for
        each interval."
    ::= { pwObjects 4 }

pwPerfIntervalEntry OBJECT-TYPE
    SYNTAX      PwPerfIntervalEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An entry in this table is created by the agent for every
        PW."
    INDEX      { pwIndex, pwPerfIntervalNumber }
    ::= { pwPerfIntervalTable 1 }

PwPerfIntervalEntry ::= SEQUENCE {
    pwPerfIntervalNumber          Integer32,
    pwPerfIntervalValidData      TruthValue,
    pwPerfIntervalTimeElapsed    HCPerfTimeElapsed,
    pwPerfIntervalInHCPackets    HCPerfIntervalCount,
    pwPerfIntervalInHCBytes      HCPerfIntervalCount,
    pwPerfIntervalOutHCPackets   HCPerfIntervalCount,
    pwPerfIntervalOutHCBytes     HCPerfIntervalCount,
    pwPerfIntervalInPackets      PerfIntervalCount,
    pwPerfIntervalInBytes        PerfIntervalCount,
    pwPerfIntervalOutPackets     PerfIntervalCount,
    pwPerfIntervalOutBytes       PerfIntervalCount
}

pwPerfIntervalNumber OBJECT-TYPE

```

SYNTAX Integer32 (1..96)
 MAX-ACCESS not-accessible
 STATUS current
 DESCRIPTION

"A number N, between 1 and 96, which identifies the interval for which the set of statistics is available. The interval identified by 1 is the most recently completed 15-minute interval, and the interval identified by N is the interval immediately preceding the one identified by N-1. The minimum range of N is 1 through 4. The default range is 1 to 32. The maximum range of N is 1 through 96."

REFERENCE

"Tesink, K. 'Definitions of Managed Objects for the SONET/SDH Interface Type', RFC 2558"

::= { pwPerfIntervalEntry 1 }

pwPerfIntervalValidData OBJECT-TYPE

SYNTAX TruthValue
 MAX-ACCESS read-only
 STATUS current
 DESCRIPTION

"This variable indicates if the data for this interval is valid."

::= { pwPerfIntervalEntry 2 }

pwPerfIntervalTimeElapsed OBJECT-TYPE

SYNTAX HCPperfTimeElapsed
 MAX-ACCESS read-only
 STATUS current
 DESCRIPTION

"The duration of this interval in seconds."

::= { pwPerfIntervalEntry 3 }

pwPerfIntervalInHCPackets OBJECT-TYPE

SYNTAX HCPperfIntervalCount
 MAX-ACCESS read-only
 STATUS current
 DESCRIPTION

"High-capacity counter for number of packets received by the PW (from the PSN) during the interval. This is the 64-bit version of pwPerfIntervalInPackets, if pwPerfIntervalInHCPackets is supported according to the rules spelled out in RFC 2863."

::= { pwPerfIntervalEntry 4 }

pwPerfIntervalInHCBytes OBJECT-TYPE

SYNTAX HCPperfIntervalCount

MAX-ACCESS read-only
STATUS current

DESCRIPTION

"High-capacity counter for number of bytes received by the PW (from the PSN) during the interval.

This is the 64-bit version of pwPerfIntervalInBytes, if pwPerfIntervalInHCBytes is supported according to the rules spelled out in RFC 2863."

::= { pwPerfIntervalEntry 5 }

pwPerfIntervalOutHCPackets OBJECT-TYPE

SYNTAX HCPerfIntervalCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"High-capacity counter for number of packets forwarded by the PW (to the PSN) during the interval.

This is the 64-bit version of pwPerfIntervalOutPackets, if pwPerfIntervalOutHCPackets is supported according to the rules spelled out in RFC 2863."

::= { pwPerfIntervalEntry 6 }

pwPerfIntervalOutHCBytes OBJECT-TYPE

SYNTAX HCPerfIntervalCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"High-capacity counter for number of bytes forwarded by the PW (to the PSN) during the interval.

This is the 64-bit version of pwPerfIntervalOutBytes, if pwPerfIntervalOutHCBytes is supported according to the rules spelled out in RFC 2863."

::= { pwPerfIntervalEntry 7 }

pwPerfIntervalInPackets OBJECT-TYPE

SYNTAX PerfIntervalCount

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This value represents the number of packets received by this PW during the interval.

It MUST be equal to the least significant 32 bits of pwPerfIntervalInHCPackets, if pwPerfIntervalInHCPackets is supported according to the rules spelled out in RFC 2863."

::= { pwPerfIntervalEntry 8 }

pwPerfIntervalInBytes OBJECT-TYPE

```

SYNTAX          PerfIntervalCount
MAX-ACCESS      read-only
STATUS          current
DESCRIPTION
    "This value represents the number of bytes received by
    this PW during the interval.  It MUST be equal to the
    least significant 32 bits of pwPerfIntervalInHCBytes, if
    pwPerfIntervalInHCBytes is supported according to the
    rules spelled out in RFC 2863."
 ::= { pwPerfIntervalEntry 9 }

```

```

pwPerfIntervalOutPackets OBJECT-TYPE
SYNTAX          PerfIntervalCount
MAX-ACCESS      read-only
STATUS          current
DESCRIPTION
    "This value represents the number of packets sent by this
    PW during the interval.
    It MUST be equal to the least significant 32 bits of
    pwPerfIntervalOutHCPackets, if
    pwPerfIntervalOutHCPackets is supported according to the
    rules spelled out in RFC 2863."
 ::= { pwPerfIntervalEntry 10 }

```

```

pwPerfIntervalOutBytes OBJECT-TYPE
SYNTAX          PerfIntervalCount
MAX-ACCESS      read-only
STATUS          current
DESCRIPTION
    "This value represents the number of bytes sent by this
    PW during the interval.
    It MUST be equal to the least significant 32
    bits of pwPerfIntervalOutHCBytes,
    if pwPerfIntervalOutHCBytes is supported according to
    the rules spelled out in RFC 2863."
 ::= { pwPerfIntervalEntry 11 }

```

```
-- End of the PW Performance Interval Table
```

```
-- PW Performance 1-day Interval Table
```

```

pwPerf1DayIntervalTable OBJECT-TYPE
SYNTAX          SEQUENCE OF PwPerf1DayIntervalEntry
MAX-ACCESS      not-accessible
STATUS          current
DESCRIPTION
    "This table provides per-PW performance information for
    the current day's measurement and the previous day's

```

```

        interval."
 ::= { pwObjects 5 }

pwPerf1DayIntervalEntry OBJECT-TYPE
    SYNTAX      PwPerf1DayIntervalEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An entry in this table is created by the agent for every
        PW."
    INDEX       { pwIndex, pwPerf1DayIntervalNumber }

 ::= { pwPerf1DayIntervalTable 1 }

PwPerf1DayIntervalEntry ::= SEQUENCE {
    pwPerf1DayIntervalNumber      Unsigned32,
    pwPerf1DayIntervalValidData  TruthValue,
    pwPerf1DayIntervalTimeElapsed HCPperfTimeElapsed,
    pwPerf1DayIntervalInHCPackets Counter64,
    pwPerf1DayIntervalInHCBytes  Counter64,
    pwPerf1DayIntervalOutHCPackets Counter64,
    pwPerf1DayIntervalOutHCBytes Counter64
}

pwPerf1DayIntervalNumber OBJECT-TYPE
    SYNTAX      Unsigned32(1..31)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "History Data Interval number. Interval 1 is the current day's
        measurement period, interval 2 is the most recent previous
        day, and interval 30 is 31 days ago. Intervals 3..31 are
        optional."
    ::= { pwPerf1DayIntervalEntry 1 }

pwPerf1DayIntervalValidData OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "This variable indicates if the data for this interval
        is valid."
    ::= { pwPerf1DayIntervalEntry 2 }

pwPerf1DayIntervalTimeElapsed OBJECT-TYPE
    SYNTAX      HCPperfTimeElapsed
    UNITS       "seconds"
    MAX-ACCESS  read-only

```

```
STATUS          current
DESCRIPTION
  "The number of seconds in the 1-day interval over which the
  performance monitoring information is actually counted.
  This value will be the same as the interval duration except
  in a situation where performance monitoring data could not
  be collected for any reason or where agent clock adjustments
  have been made."
 ::= { pwPerflDayIntervalEntry 3 }

pwPerflDayIntervalInHCPackets OBJECT-TYPE
SYNTAX          Counter64
MAX-ACCESS      read-only
STATUS          current
DESCRIPTION
  "High-capacity counter for the total number of packets
  received by the PW (from the PSN)."
 ::= { pwPerflDayIntervalEntry 4 }

pwPerflDayIntervalInHCBytes OBJECT-TYPE
SYNTAX          Counter64
MAX-ACCESS      read-only
STATUS          current
DESCRIPTION
  "High-capacity counter for the total number of bytes
  received by the PW (from the PSN)."
 ::= { pwPerflDayIntervalEntry 5 }

pwPerflDayIntervalOutHCPackets OBJECT-TYPE
SYNTAX          Counter64
MAX-ACCESS      read-only
STATUS          current
DESCRIPTION
  "High-capacity counter for the total number of packets
  forwarded by the PW (to the PSN)."
 ::= { pwPerflDayIntervalEntry 6 }

pwPerflDayIntervalOutHCBytes OBJECT-TYPE
SYNTAX          Counter64
MAX-ACCESS      read-only
STATUS          current
DESCRIPTION
  "High-capacity counter for the total number of bytes
  forwarded by the PW (to the PSN)."
 ::= { pwPerflDayIntervalEntry 7 }

-- End of the PW Performance 1-day Interval Table
```

```

-- Error counter scalar

pwPerfTotalErrorPackets OBJECT-TYPE
    SYNTAX          Counter32
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
        "Counter for number of errors at the PW processing level,
         for example, packets received with unknown PW label."
    ::= { pwObjects 6 }

-- Reverse mapping tables

-- The PW ID mapping table
pwIndexMappingTable OBJECT-TYPE
    SYNTAX          SEQUENCE OF PwIndexMappingEntry
    MAX-ACCESS      not-accessible
    STATUS          current
    DESCRIPTION
        "This table enables the reverse mapping of the unique
         PwId parameters [peer IP, PW type, and PW ID] and the
         pwIndex.  The table is not applicable for PWs created
         manually or by using the generalized FEC."
    ::= { pwObjects 7 }

pwIndexMappingEntry OBJECT-TYPE
    SYNTAX          PwIndexMappingEntry
    MAX-ACCESS      not-accessible
    STATUS          current
    DESCRIPTION
        "An entry in this table MUST be created by the agent for
         every PW created by the pwTable for which pwOwner
         equals pwIdFecSignaling and pwID is not zero.

         Implementers need to be aware that if the value of
         the pwIndexMappingPeerAddr (an OID) has more than
         113 sub-identifiers, then OIDs of column instances
         in this table will have more than 128 sub-identifiers
         and cannot be accessed using SNMPv1, SNMPv2c, or SNMPv3."
    INDEX          { pwIndexMappingPwType, pwIndexMappingPwID,
                    pwIndexMappingPeerAddrType, pwIndexMappingPeerAddr
                    }
    ::= { pwIndexMappingTable 1 }

PwIndexMappingEntry ::= SEQUENCE {
    pwIndexMappingPwType      IANAPwTypeTC,
    pwIndexMappingPwID        PwIDType,
    pwIndexMappingPeerAddrType InetAddressType,

```



```

    pwIndexMappingPeerAddr      InetAddress,
    pwIndexMappingPwIndex      PwIndexType
    }

```

pwIndexMappingPwType OBJECT-TYPE

```

SYNTAX      IANAPwTypeTC
MAX-ACCESS  not-accessible
STATUS      current

```

DESCRIPTION

"The PW type (indicates the service) of this PW."

```
 ::= { pwIndexMappingEntry 1 }
```

pwIndexMappingPwID OBJECT-TYPE

```

SYNTAX      PwIDType
MAX-ACCESS  not-accessible
STATUS      current

```

DESCRIPTION

"The PW ID of this PW. Zero if the PW is configured manually."

```
 ::= { pwIndexMappingEntry 2 }
```

pwIndexMappingPeerAddrType OBJECT-TYPE

```

SYNTAX      InetAddressType
MAX-ACCESS  not-accessible
STATUS      current

```

DESCRIPTION

"IP address type of the peer node."

```
 ::= { pwIndexMappingEntry 3 }
```

pwIndexMappingPeerAddr OBJECT-TYPE

```

SYNTAX      InetAddress
MAX-ACCESS  not-accessible
STATUS      current

```

DESCRIPTION

"IP address of the peer node."

```
 ::= { pwIndexMappingEntry 4 }
```

pwIndexMappingPwIndex OBJECT-TYPE

```

SYNTAX      PwIndexType
MAX-ACCESS  read-only
STATUS      current

```

DESCRIPTION

"The value that represents the PW in the pwTable."

```
 ::= { pwIndexMappingEntry 5 }
```

-- End of the PW ID mapping table

-- The peer mapping table

```

pwPeerMappingTable OBJECT-TYPE
    SYNTAX          SEQUENCE OF PwPeerMappingEntry
    MAX-ACCESS      not-accessible
    STATUS          current
    DESCRIPTION
        "This table provides reverse mapping of the existing PW
        based on PW type and PW ID ordering. This table is
        typically useful for the element management system (EMS)
        ordered query of existing PWs."
    ::= { pwObjects 8 }

```

```

pwPeerMappingEntry OBJECT-TYPE
    SYNTAX          PwPeerMappingEntry
    MAX-ACCESS      not-accessible
    STATUS          current
    DESCRIPTION
        "An entry in this table is created by the agent for every
        PW entry in the pwTable.

        Implementers need to be aware that if the value of the
        pwPeerMappingPeerAddr (an OID) has more than 113
        sub-identifiers, then OIDs of column instances in this
        table will have more than 128 sub-identifiers and cannot
        be accessed using SNMPv1, SNMPv2c, or SNMPv3."
    INDEX { pwPeerMappingPeerAddrType, pwPeerMappingPeerAddr,
            pwPeerMappingPwType, pwPeerMappingPwID }

    ::= { pwPeerMappingTable 1 }

```

```

PwPeerMappingEntry ::= SEQUENCE {
    pwPeerMappingPeerAddrType      InetAddressType,
    pwPeerMappingPeerAddr         InetAddress,
    pwPeerMappingPwType           IANAPwTypeTC,
    pwPeerMappingPwID             PwIDType,
    pwPeerMappingPwIndex          PwIndexType
}

```

```

pwPeerMappingPeerAddrType OBJECT-TYPE
    SYNTAX          InetAddressType
    MAX-ACCESS      not-accessible
    STATUS          current
    DESCRIPTION
        "IP address type of the peer node."
    ::= { pwPeerMappingEntry 1 }

```

```

pwPeerMappingPeerAddr OBJECT-TYPE
    SYNTAX          InetAddress
    MAX-ACCESS      not-accessible

```

```

STATUS          current
DESCRIPTION
  "IP address of the peer node."
 ::= { pwPeerMappingEntry 2 }

```

```

pwPeerMappingPwType OBJECT-TYPE
SYNTAX          IANAPwTypeTC
MAX-ACCESS     not-accessible
STATUS         current
DESCRIPTION
  "The PW type (indicates the emulated service) of this PW."
 ::= { pwPeerMappingEntry 3 }

```

```

pwPeerMappingPwID OBJECT-TYPE
SYNTAX          PwIDType
MAX-ACCESS     not-accessible
STATUS         current
DESCRIPTION
  "The PW ID of this PW.  Zero if the PW is configured
  manually."
 ::= { pwPeerMappingEntry 4 }

```

```

pwPeerMappingPwIndex OBJECT-TYPE
SYNTAX          PwIndexType
MAX-ACCESS     read-only
STATUS         current
DESCRIPTION
  "The value that represents the PW in the pwTable."
 ::= { pwPeerMappingEntry 5 }

```

-- End of the peer mapping table

-- End of the reverse mapping tables

```

pwUpDownNotifEnable OBJECT-TYPE
SYNTAX          TruthValue
MAX-ACCESS     read-write
STATUS         current
DESCRIPTION
  "If this object is set to true(1), then it enables
  the emission of pwUp and pwDown
  notifications; otherwise, these notifications are not
  emitted."
REFERENCE
  "See also [RFC3413] for explanation that
  notifications are under the ultimate control of the
  MIB module in this document."
DEFVAL { false }

```

```
 ::= { pwObjects 9 }

pwDeletedNotifEnable OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "If this object is set to true(1), then it enables the
        emission of pwDeleted notification; otherwise, this
        notification is not emitted."
    REFERENCE
        "See also [RFC3413] for explanation that
        notifications are under the ultimate control of the
        MIB module in this document."
    DEFVAL { false }
    ::= { pwObjects 10 }

pwNotifRate OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "This object defines the maximum number of PW notifications
        that can be emitted from the device per second."
    ::= { pwObjects 11 }

-- The Gen Fec PW ID mapping table

pwGenFecIndexMappingTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF PwGenFecIndexMappingEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table enables the reverse mapping of the unique
        PwId parameters [GroupAttachmentID, LocalAttachmentID,
        and PeerAttachmentID] and the pwIndex. The table is
        only applicable for PW using the generalized FEC."
    ::= { pwObjects 12 }

pwGenFecIndexMappingEntry OBJECT-TYPE
    SYNTAX      PwGenFecIndexMappingEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An entry in this table MUST be created by the agent for
        every PW created by the pwTable for which pwOwner
        equals genFecSignaling.
```

Implementers need to be aware that if the combined value of pwGenFecIndexMappingAGI, pwGenFecIndexMappingLocalAII, and pwGenFecIndexMappingRemoteAII (OIDs) has more than 113 sub-identifiers, then OIDs of column instances in this table will have more than 128 sub-identifiers and cannot be accessed using SNMPv1, SNMPv2c, or SNMPv3."

```

INDEX { pwGenFecIndexMappingAGIType,
        pwGenFecIndexMappingAGI,
        pwGenFecIndexMappingLocalAIIType,
        pwGenFecIndexMappingLocalAII,
        pwGenFecIndexMappingRemoteAIIType,
        pwGenFecIndexMappingRemoteAII
      }
 ::= { pwGenFecIndexMappingTable 1 }

PwGenFecIndexMappingEntry ::= SEQUENCE {
    pwGenFecIndexMappingAGIType      PwGenIdType,
    pwGenFecIndexMappingAGI          PwAttachmentIdentifierType,
    pwGenFecIndexMappingLocalAIIType PwGenIdType,
    pwGenFecIndexMappingLocalAII     PwAttachmentIdentifierType,
    pwGenFecIndexMappingRemoteAIIType PwGenIdType,
    pwGenFecIndexMappingRemoteAII    PwAttachmentIdentifierType,
    pwGenFecIndexMappingPwIndex      PwIndexType
  }

pwGenFecIndexMappingAGIType OBJECT-TYPE
    SYNTAX      PwGenIdType
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This object is the type of the attachment
         group identifier (AGI) that this PW belongs to."
    ::= { pwGenFecIndexMappingEntry 1 }

pwGenFecIndexMappingAGI OBJECT-TYPE
    SYNTAX      PwAttachmentIdentifierType
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This object is an octet string representing the attachment
         group identifier (AGI) that this PW belongs to,
         which typically identifies the VPN ID."
    ::= { pwGenFecIndexMappingEntry 2 }

pwGenFecIndexMappingLocalAIIType OBJECT-TYPE
    SYNTAX      PwGenIdType
    MAX-ACCESS  not-accessible
    STATUS      current

```

DESCRIPTION

"This object is the type of the local forwarder attachment individual identifier (AII) to be used by this PW."

::= { pwGenFecIndexMappingEntry 3 }

pwGenFecIndexMappingLocalAII OBJECT-TYPE

SYNTAX PwAttachmentIdentifierType

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This object is an octet string representing the local forwarder attachment individual identifier (AII) to be used by this PW. It is used as the SAI for outgoing signaling messages and the TAI in the incoming messages from the peer."

::= { pwGenFecIndexMappingEntry 4 }

pwGenFecIndexMappingRemoteAIIType OBJECT-TYPE

SYNTAX PwGenIdType

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This object is the type of the remote forwarder attachment individual identifier (AII) to be used by this PW."

::= { pwGenFecIndexMappingEntry 5 }

pwGenFecIndexMappingRemoteAII OBJECT-TYPE

SYNTAX PwAttachmentIdentifierType

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This object is an octet string representing the peer forwarder attachment individual identifier (AII) to be used by this PW. It is used as the TAI for outgoing signaling messages and the SAI in the incoming messages from the peer."

::= { pwGenFecIndexMappingEntry 6 }

pwGenFecIndexMappingPwIndex OBJECT-TYPE

SYNTAX PwIndexType

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The value that represents the PW in the pwTable."

::= { pwGenFecIndexMappingEntry 7 }

-- End of the Gen Fec PW ID mapping table

-- Notifications - PW

pwDown NOTIFICATION-TYPE

```
OBJECTS { pwOperStatus, --start of range
          pwOperStatus  --end of range
        }
```

STATUS current

DESCRIPTION

"This notification is generated when the pwOperStatus object for one or more contiguous entries in the pwTable are about to enter the down(2) or lowerLayerDown(6) state from any other state, except for transition from the notPresent(5) state. For the purpose of deciding when these notifications occur, the lowerLayerDown(6) state and the down(2) state are considered to be equivalent; i.e., there is no notification on transition from lowerLayerDown(6) into down(2), and there is a trap on transition from any other state except down(2) (and notPresent) into lowerLayerDown(6).

The included values of pwOperStatus MUST each be equal to down(2) or lowerLayerDown(6). The two instances of pwOperStatus in this notification indicate the range of indexes that are affected. Note that all the indexes of the two ends of the range can be derived from the instance identifiers of these two objects. For cases where a contiguous range of cross-connects have transitioned into the down(2) and lowerLayerDown(6) states at roughly the same time, the device SHOULD issue a single notification for each range of contiguous indexes in an effort to minimize the emission of a large number of notifications. If a notification has to be issued for just a single cross-connect entry, then the instance identifier (and values) of the two pwOperStatus objects MUST be identical."

```
::= { pwNotifications 1 }
```

pwUp NOTIFICATION-TYPE

```
OBJECTS { pwOperStatus, --start of range
          pwOperStatus  --end of range
        }
```

STATUS current

DESCRIPTION

"This notification is generated when the pwOperStatus object for one or more contiguous entries in the pwTable are about to enter the up(1) state from some other state

```

except the notPresent(5) state and given that the pwDown
notification been issued for these entries. The included
values of pwOperStatus MUST both be set equal to this
new state (i.e., up(1)). The two instances of pwOperStatus
in this notification indicate the range of indexes that
are affected. Note that all the indexes of the two ends
of the range can be derived from the instance identifiers
of these two objects. For cases where a contiguous range
of cross-connects have transitioned into the up(1) state
at roughly the same time, the device SHOULD issue a single
notification for each range of contiguous indexes in an
effort to minimize the emission of a large number of
notifications. If a notification has to be issued for
just a single cross-connect entry, then the instance
identifier (and values) of the two pwOperStatus objects
MUST be identical."
 ::= { pwNotifications 2 }

pwDeleted NOTIFICATION-TYPE
OBJECTS { pwType,
          pwID,
          pwPeerAddrType,
          pwPeerAddr
        }
STATUS current
DESCRIPTION
  "This notification is generated when the PW has been
  deleted, i.e., when the pwRowStatus has been set to
  destroy(6) or the PW has been deleted by a non-MIB
  application or due to an auto-discovery process.
  "
 ::= { pwNotifications 3 }

-- End of notifications.

-- Conformance information

pwGroups      OBJECT IDENTIFIER ::= { pwConformance 1 }
pwCompliances OBJECT IDENTIFIER ::= { pwConformance 2 }

-- Compliance requirement for fully compliant implementations

pwModuleFullCompliance MODULE-COMPLIANCE
STATUS current
DESCRIPTION
  "The compliance statement for agents that provide full
  support for the PW MIB module. Such devices can
  then be monitored and configured using

```


this MIB module."

```
MODULE -- this module
  MANDATORY-GROUPS { pwBasicGroup,
                    pwPerformanceGeneralGroup
                  }

GROUP pwNotificationGroup
DESCRIPTION "This group is only mandatory for implementations
            that can efficiently implement the notifications
            contained in this group.
            "

GROUP      pwPwIdGroup
DESCRIPTION "This group is only mandatory for implementations
            that support the PW ID FEC.
            "

GROUP      pwGeneralizedFecGroup
DESCRIPTION "This group is only mandatory for implementations
            that support the generalized PW FEC.
            "

GROUP      pwFcsGroup
DESCRIPTION "This group is only mandatory for implementations
            that support FCS retention."

GROUP      pwFragGroup
DESCRIPTION "This group is only mandatory for implementations
            that support PW fragmentation.
            "

GROUP      pwPwStatusGroup
DESCRIPTION "This group is only mandatory for implementations
            that support PW status notification.
            "

GROUP      pwGetNextGroup
DESCRIPTION "This group is only mandatory for implementations
            where the pwIndex may be any arbitrary value
            and the EMS would require retrieval of the next
            free index."

GROUP      pwPriorityGroup
DESCRIPTION "This group is only mandatory for implementations
            that support the controlling the PW setup and
            holding priority."
```

GROUP pwAttachmentGroup
DESCRIPTION "This group is only mandatory for implementations that support attachment of two PWs (PW stitching)."

GROUP pwPerformance1DayIntervalGroup
DESCRIPTION "This group is only mandatory for implementations that support PW performance gathering in 1-day intervals."

GROUP pwPerformanceIntervalGeneralGroup
DESCRIPTION "This group is only mandatory for implementations that support PW performance gathering in 15-minute intervals."

GROUP pwPerformanceIntervalGroup
DESCRIPTION "This group is only mandatory for implementations that support PW performance gathering in 15-minute intervals."

GROUP pwHCPeformanceIntervalGroup
DESCRIPTION "This group is only mandatory for implementations where at least one of the interval performance counters wraps around too quickly based on the criteria specified in RFC 2863 for high-capacity counters."

GROUP pwMappingTablesGroup
DESCRIPTION "This group is only mandatory for implementations that support reverse mapping of PW indexes to the pwIndex and the peer mapping table."

GROUP pwSignalingGroup
DESCRIPTION "This group is only mandatory for implementations that support the PW signaling."

GROUP pwNotificationControlGroup
DESCRIPTION "This group is only mandatory for implementations that support the PW notifications."

OBJECT pwAdminStatus
SYNTAX INTEGER { up(1), down(2) }
DESCRIPTION "Support of the value testing(3) is not required."

OBJECT pwOperStatus
SYNTAX INTEGER { up(1), down(2), notPresent(5), lowerLayerDown(6) }
DESCRIPTION "Support of the values testing(3) and dormant(4)

is not required."

OBJECT pwRowStatus
 SYNTAX RowStatus { active(1), notInService(2),
 notReady(3) }
 WRITE-SYNTAX RowStatus { active(1), notInService(2),
 createAndGo(4), destroy(6)
 }
 DESCRIPTION "Support for createAndWait is not required. Support
 of notReady is not required for implementations
 that do not support signaling, or if it is
 guaranteed that the conceptual row has all the
 required information to create the PW when the
 row has been created by the agent or written by
 the operator."

OBJECT pwPeerAddrType
 SYNTAX InetAddressType { unknown(0), ipv4(1) }
 MIN-ACCESS read-only
 DESCRIPTION "Only unknown(0) and ipv4(1) are required.
 Implementations that support only IPv4 MAY support
 read-only access."

OBJECT pwPeerAddr
 SYNTAX InetAddress (SIZE(0|4))
 DESCRIPTION "An implementation is only required to support
 0, 4 address sizes."

OBJECT pwStorageType
 MIN-ACCESS read-only
 DESCRIPTION "Write access is not required."

OBJECT pwNotifRate
 MIN-ACCESS read-only
 DESCRIPTION "Write access is not required."

::= { pwCompliances 1 }

-- Compliance requirement for read-only compliant implementations

pwModuleReadOnlyCompliance MODULE-COMPLIANCE
 STATUS current
 DESCRIPTION
 "The compliance statement for agents that provide read-
 only support for the PW MIB module. Such devices can
 then be monitored but cannot be configured using this
 MIB module."

```
MODULE -- this module
  MANDATORY-GROUPS { pwBasicGroup
                    }

GROUP      pwNotificationGroup
DESCRIPTION "This group is only mandatory for implementations
            that can efficiently implement the notifications
            contained in this group."

GROUP      pwPwIdGroup
DESCRIPTION "This group is only mandatory for implementations
            that support the PW ID FEC.
            "

GROUP      pwGeneralizedFecGroup
DESCRIPTION "This group is only mandatory for implementations
            that support the generalized PW FEC.
            "

GROUP      pwFcsGroup
DESCRIPTION "This group is only mandatory for implementations
            that support FCS retention."

GROUP      pwFragGroup
DESCRIPTION "This group is only mandatory for implementations
            that support PW fragmentation.
            "

GROUP      pwPwStatusGroup
DESCRIPTION "This group is only mandatory for implementations
            that support PW status notification.
            "

GROUP      pwGetNextGroup
DESCRIPTION "This group is only mandatory for implementations
            where the pwIndex may be any arbitrary value
            and the EMS would require retrieval of the next
            free index."

GROUP      pwPriorityGroup
DESCRIPTION "This group is only mandatory for implementations
            that support the controlling the PW setup and
            holding priority."

GROUP      pwAttachmentGroup
DESCRIPTION "This group is only mandatory for implementations
            that support attachment of two PWs (PW stitching)."
```

GROUP pwPerformance1DayIntervalGroup
DESCRIPTION "This group is only mandatory for implementations that support PW performance gathering in 1-day intervals."

GROUP pwPerformanceIntervalGeneralGroup
DESCRIPTION "This group is only mandatory for implementations that support PW performance gathering in 15-minute intervals."

GROUP pwPerformanceIntervalGroup
DESCRIPTION "This group is only mandatory for implementations that support PW performance gathering in 15-minute intervals."

GROUP pwHCPeformanceIntervalGroup
DESCRIPTION "This group is only mandatory for implementations where at least one of the interval performance counters wraps around too quickly based on the criteria specified in RFC 2863 for high-capacity counters."

GROUP pwMappingTablesGroup
DESCRIPTION "This group is only mandatory for implementations that support reverse mapping of PW indexes to the pwIndex and the peer mapping table."

GROUP pwSignalingGroup
DESCRIPTION "This group is only mandatory for implementations that support the PW signaling."

GROUP pwNotificationControlGroup
DESCRIPTION "This group is only mandatory for implementations that support the PW notifications."

OBJECT pwType
MIN-ACCESS read-only
DESCRIPTION "Write access is not required."

OBJECT pwOwner
MIN-ACCESS read-only
DESCRIPTION "Write access is not required."

OBJECT pwPsnType
MIN-ACCESS read-only
DESCRIPTION "Write access is not required."

OBJECT pwSetUpPriority

MIN-ACCESS read-only
DESCRIPTION "Write access is not required."

OBJECT pwHoldingPriority
MIN-ACCESS read-only
DESCRIPTION "Write access is not required."

OBJECT pwPeerAddrType
SYNTAX InetAddressType { unknown(0), ipv4(1) }
MIN-ACCESS read-only
DESCRIPTION "Write access is not required. Only unknown(0) and ipv4(1) are required."

OBJECT pwPeerAddr
SYNTAX InetAddress (SIZE(0|4))
MIN-ACCESS read-only
DESCRIPTION "Write access is not required. An implementation is only required to support 0, 4 address sizes."

OBJECT pwAttachedPwIndex
MIN-ACCESS read-only
DESCRIPTION "Write access is not required."

OBJECT pwIfIndex
MIN-ACCESS read-only
DESCRIPTION "Write access is not required."

OBJECT pwID
MIN-ACCESS read-only
DESCRIPTION "Write access is not required."

OBJECT pwLocalGroupID
MIN-ACCESS read-only
DESCRIPTION "Write access is not required."

OBJECT pwGroupAttachmentID
MIN-ACCESS read-only
DESCRIPTION "Write access is not required."

OBJECT pwLocalAttachmentID
MIN-ACCESS read-only
DESCRIPTION "Write access is not required."

OBJECT pwRemoteAttachmentID
MIN-ACCESS read-only
DESCRIPTION "Write access is not required."

OBJECT pwCwPreference

MIN-ACCESS read-only
DESCRIPTION "Write access is not required."

OBJECT pwLocalIfMtu
MIN-ACCESS read-only
DESCRIPTION "Write access is not required."

OBJECT pwLocalIfString
MIN-ACCESS read-only
DESCRIPTION "Write access is not required."

OBJECT pwLocalCapabAdvert
MIN-ACCESS read-only
DESCRIPTION "Write access is not required."

OBJECT pwFragmentCfgSize
MIN-ACCESS read-only
DESCRIPTION "Write access is not required."

OBJECT pwFcsRetentionCfg
MIN-ACCESS read-only
DESCRIPTION "Write access is not required."

OBJECT pwOutboundLabel
MIN-ACCESS read-only
DESCRIPTION "Write access is not required."

OBJECT pwInboundLabel
MIN-ACCESS read-only
DESCRIPTION "Write access is not required."

OBJECT pwName
MIN-ACCESS read-only
DESCRIPTION "Write access is not required."

OBJECT pwDescr
MIN-ACCESS read-only
DESCRIPTION "Write access is not required."

OBJECT pwAdminStatus
SYNTAX INTEGER { up(1), down(2) }
MIN-ACCESS read-only
DESCRIPTION "Write access is not required. The support of value testing(3) is not required."

OBJECT pwOperStatus
SYNTAX INTEGER { up(1), down(2), notPresent(5), lowerLayerDown(6) }

DESCRIPTION "The support of the values testing(3) and dormant(4) is not required."

OBJECT pwRowStatus
SYNTAX RowStatus { active(1) }
MIN-ACCESS read-only
DESCRIPTION "Write access is not required."

OBJECT pwStorageType
MIN-ACCESS read-only
DESCRIPTION "Write access is not required."

OBJECT pwOamEnable
MIN-ACCESS read-only
DESCRIPTION "Write access is not required."

OBJECT pwGenAGIType
MIN-ACCESS read-only
DESCRIPTION "Write access is not required."

OBJECT pwGenLocalAIIType
MIN-ACCESS read-only
DESCRIPTION "Write access is not required."

OBJECT pwGenRemoteAIIType
MIN-ACCESS read-only
DESCRIPTION "Write access is not required."

OBJECT pwUpDownNotifEnable
MIN-ACCESS read-only
DESCRIPTION "Write access is not required."

OBJECT pwDeletedNotifEnable
MIN-ACCESS read-only
DESCRIPTION "Write access is not required."

OBJECT pwNotifRate
MIN-ACCESS read-only
DESCRIPTION "Write access is not required."

::= { pwCompliances 2 }

-- Units of conformance.

pwBasicGroup OBJECT-GROUP
OBJECTS {
 pwType,
 pwOwner,


```

    pwPsnType,
    pwIfIndex,
    pwCwPreference,
    pwLocalIfMtu,
    pwOutboundLabel,
    pwInboundLabel,
    pwName,
    pwDescr,
    pwCreateTime,
    pwUpTime,
    pwLastChange,
    pwAdminStatus,
    pwOperStatus,
    pwLocalStatus,
    pwRowStatus,
    pwStorageType,
    pwOamEnable
}

```

STATUS current

DESCRIPTION

"Collection of objects that are required in all implementations that support the PW MIB module."

::= { pwGroups 1 }

pwPwIdGroup OBJECT-GROUP

```

OBJECTS {
    pwID
}

```

STATUS current

DESCRIPTION

"Collection of objects required for PW ID configuration and signaling."

::= { pwGroups 2 }

pwGeneralizedFecGroup OBJECT-GROUP

```

OBJECTS {
    pwGroupAttachmentID,
    pwLocalAttachmentID,
    pwRemoteAttachmentID,
    pwGenAGIType,
    pwGenLocalAIIType,
    pwGenRemoteAIIType
}

```

STATUS current

DESCRIPTION

"Collection of objects required for generalized FEC"

```
        configuration and signaling."
 ::= { pwGroups 3 }

pwFcsGroup    OBJECT-GROUP
OBJECTS {
    pwFcsRetentionCfg,
    pwFcsRetentionStatus
}

STATUS current
DESCRIPTION
    "Collection of objects required for FCS retention
    configuration and signaling."
 ::= { pwGroups 4 }

pwFragGroup    OBJECT-GROUP
OBJECTS {
    pwFragmentCfgSize,
    pwRmtFragCapability
}

STATUS current
DESCRIPTION
    "Collection of objects required for fragmentation
    configuration and signaling."
 ::= { pwGroups 5 }

pwPwStatusGroup    OBJECT-GROUP
OBJECTS {
    pwRemoteCapabilities,
    pwRemoteStatusCapable,
    pwRemoteStatus
}

STATUS current
DESCRIPTION
    "Collection of objects required for PW status configuration
    and signaling."
 ::= { pwGroups 6 }

pwGetNextGroup    OBJECT-GROUP
OBJECTS {
    pwIndexNext
}

STATUS current
DESCRIPTION
    "Collection of objects for getting the next available
```

```
        index."
 ::= { pwGroups 7 }

pwPriorityGroup OBJECT-GROUP
OBJECTS {
    pwSetUpPriority,
    pwHoldingPriority
}

STATUS current
DESCRIPTION
    "Collection of objects for controlling the PW setup and
    holding priority."
 ::= { pwGroups 8 }

pwAttachmentGroup OBJECT-GROUP
OBJECTS {
    pwAttachedPwIndex
}

STATUS current
DESCRIPTION
    "Collection of objects for PW configuration as ifIndex."
 ::= { pwGroups 9 }

pwPerformanceGeneralGroup OBJECT-GROUP
OBJECTS {
    pwPerfTotalErrorPackets
}

STATUS current
DESCRIPTION
    "Collection of general objects needed for managing the
    total running performance parameters."
 ::= { pwGroups 10 }

pwPerformance1DayIntervalGroup OBJECT-GROUP
OBJECTS {
    pwPerf1DayIntervalValidData,
    pwPerf1DayIntervalTimeElapsed,
    pwPerf1DayIntervalInHCPackets,
    pwPerf1DayIntervalInHCBytes,
    pwPerf1DayIntervalOutHCPackets,
    pwPerf1DayIntervalOutHCBytes
}

STATUS current
DESCRIPTION
    "Collection of objects needed for a PW running 1-day
```

```
        interval performance collection."
 ::= { pwGroups 11 }

pwPerformanceIntervalGeneralGroup OBJECT-GROUP
OBJECTS {
    pwTimeElapsed,
    pwValidIntervals,
    pwPerfIntervalValidData,
    pwPerfIntervalTimeElapsed
}

STATUS current
DESCRIPTION
    "Collection of general objects needed for managing the
    interval performance parameters."
 ::= { pwGroups 12 }

pwPerformanceIntervalGroup OBJECT-GROUP
OBJECTS {
    pwPerfCurrentInPackets,
    pwPerfCurrentInBytes,
    pwPerfCurrentOutPackets,
    pwPerfCurrentOutBytes,

    pwPerfIntervalInPackets,
    pwPerfIntervalInBytes,
    pwPerfIntervalOutPackets,
    pwPerfIntervalOutBytes
}

STATUS current
DESCRIPTION
    "Collection of 32-bit objects needed for PW performance
    collection in 15-minute intervals."
 ::= { pwGroups 13 }

pwHCPeformanceIntervalGroup OBJECT-GROUP
OBJECTS {
    pwPerfCurrentInHCPackets,
    pwPerfCurrentInHCBytes,
    pwPerfCurrentOutHCPackets,
    pwPerfCurrentOutHCBytes,

    pwPerfIntervalInHCPackets,
    pwPerfIntervalInHCBytes,
    pwPerfIntervalOutHCPackets,
    pwPerfIntervalOutHCBytes
}
```

```
STATUS current
DESCRIPTION
    "Collection of HC objects needed for PW performance
    collection in 15-minute intervals."
 ::= { pwGroups 14 }
```

```
pwMappingTablesGroup OBJECT-GROUP
OBJECTS {
    pwIndexMappingPwIndex,
    pwPeerMappingPwIndex,
    pwGenFecIndexMappingPwIndex
}
```

```
STATUS current
DESCRIPTION
    "Collection of objects contained in the reverse
    mapping tables."
 ::= { pwGroups 15 }
```

```
pwNotificationControlGroup OBJECT-GROUP
OBJECTS {
    pwUpDownNotifEnable,
    pwDeletedNotifEnable,
    pwNotifRate
}
```

```
STATUS current
DESCRIPTION
    "Collection of objects for controlling the PW
    notifications."
 ::= { pwGroups 16 }
```

```
pwNotificationGroup NOTIFICATION-GROUP
NOTIFICATIONS {
    pwUp,
    pwDown,
    pwDeleted
}
```

```
STATUS current
DESCRIPTION
    "Collection of PW notifications objects."
 ::= { pwGroups 17 }
```

```
pwSignalingGroup OBJECT-GROUP
OBJECTS {
    pwPeerAddrType,
    pwPeerAddr,
}
```

```

        pwLocalGroupID,
        pwLocalIfString,
        pwLocalCapabAdvert,
        pwRemoteGroupID,
        pwCwStatus,
        pwRemoteIfMtu,
        pwRemoteIfString
    }

STATUS    current
DESCRIPTION
    "Collection of objects for use in implementations that
    support the PW signaling."
 ::= { pwGroups 18 }

```

END

13. Security Considerations

It is clear that this MIB module is potentially useful for monitoring PW-capable PEs. This MIB module can also be used for configuration of certain objects, and anything that can be configured can be incorrectly configured, with potentially disastrous results.

There are a number of management objects defined in this MIB module with a MAX-ACCESS clause of read-write and/or read-create. Such objects may be considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations. These are the tables and objects and their sensitivity/vulnerability:

- o the pwTable contains objects to configure PW parameters on a Provider Edge (PE) device. Unauthorized access to objects in this table could result in disruption of traffic on the network. The objects pwUpDownNotifEnable and pwNotifRate control the reports from the network element to the EMS. Unauthorized access to these objects could result in disruption of configuration and status change reporting, resulting mis-view of the network conditions. The use of stronger mechanisms such as SNMPv3 security should be considered where possible. Specifically, SNMPv3 VACM and USM MUST be used with any v3 agent that implements this MIB module. Administrators should consider whether read access to these objects should be allowed, since read access may be undesirable under certain circumstances.

Some of the readable objects in this MIB module (i.e., objects with a MAX-ACCESS other than not-accessible) may be considered sensitive or vulnerable in some network environments. It is thus important to control even GET and/or NOTIFY access to these objects and possibly to even encrypt the values of these objects when sending them over the network via SNMP. These are the tables and objects and their sensitivity/vulnerability:

- o the pwTable, pwPerfCurrentTable, pwPerfIntervalTable, pwPerf1DayIntervalTable, pwIndexMappingTable, pwPeerMappingTable, and pwGenFecIndexMappingTable collectively show the pseudowire connectivity topology and its performance characteristics. If an administrator does not want to reveal this information, then these tables should be considered sensitive/vulnerable.

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPsec), even then, there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB module.

It is RECOMMENDED that implementers consider the security features as provided by the SNMPv3 framework (see [RFC3410], section 8), including full support for the SNMPv3 cryptographic mechanisms (for authentication and privacy).

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

14. IANA Considerations

14.1. ifType for PW

IANA has assigned a value (246) for PW in the IANAifType-MIB called ifPwType.

14.2. PW MIB Modules OBJECT IDENTIFIER Values

A PW may appear as ifIndex in the ifTable, and therefore the pwStdMIB OBJECT IDENTIFIER has been assigned under the 'transmission' subtree, as the common practice in assigning OBJECT IDENTIFIERS for MIB modules representing entities in the ifTable.

All other MIB modules related to PW management SHOULD be assigned under the 'mib-2' subtree; individual requests will appear in the MIB module memo's IANA Considerations section.

14.3. IANA Considerations for PW-STD-MIB

The MIB module in this document uses the following IANA-assigned OBJECT IDENTIFIER values recorded in the SMI Numbers registry:

Descriptor -----	OBJECT IDENTIFIER value -----
pwStdMIB	{ transmission 246 }

14.4. IANA Considerations for IANA-PWE3-MIB

The MIB module in this document uses the following IANA-assigned OBJECT IDENTIFIER values recorded in the SMI Numbers registry:

Descriptor -----	OBJECT IDENTIFIER value -----
ianaPwe3MIB	{ mib-2 174 }

15. Acknowledgments

We thank Orly Nicklass for her dedicated review and significant edit in various sections of the document, and Kiran Koushik for his contribution.

The individuals listed below contributed significantly to this document:

Dave Danenberg - Litchfield Communications
Sharon Mantin - Corrigent Systems

16. References

16.1. Normative References

- [BCP14] Bradner, S., "Key words for use in RFCs to Indicate requirement Levels", BCP 14, RFC 2119, March 1997.
- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIV2)", STD 58, RFC 2578, April 1999.

- [RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIV2", STD 58, RFC 2579, April 1999.
- [RFC2580] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Conformance Statements for SMIV2", STD 58, RFC 2580, April 1999.
- [RFC2863] McCloghrie, K. and F. Kastenholtz, "The Interfaces Group MIB", RFC 2863, June 2000.
- [RFC3411] Harrington, D., Presuhn, R., and B. Wijnen, "An Architecture for Describing Simple Network Management Protocol (SNMP) Management Frameworks", STD 62, RFC 3411, December 2002.
- [RFC3413] Levi, D., Meyer, P., and B. Stewart, "Simple Network Management Protocol (SNMP) Applications", STD 62, RFC 3413, December 2002.
- [RFC3593] Tesink, K., Ed., "Textual Conventions for MIB Modules Using Performance History Based on 15 Minute Intervals", RFC 3593, September 2003.
- [RFC3705] Ray, B. and R. Abbi, "High Capacity Textual Conventions for MIB Modules Using Performance History Based on 15 Minute Intervals", RFC 3705, February 2004.
- [RFC3931] Lau, J., Townsley, M., and I. Goyret, "Layer Two Tunneling Protocol - Version 3 (L2TPv3)", RFC 3931, March 2005.
- [RFC4001] Daniele, M., Haberman, B., Routhier, S., and J. Schoenwaelder, "Textual Conventions for Internet Network Addresses", RFC 4001, February 2005.
- [RFC4446] Martini, L., "IANA Allocations for Pseudowire Edge to Edge Emulation (PWE3)", BCP 116, RFC 4446, April 2006.
- [RFC4447] Martini, L., Rosen, E., El-Aawar, N., Smith, T., and G. Heron, "Pseudowire Setup and Maintenance Using the Label Distribution Protocol (LDP)", RFC 4447, April 2006.
- [RFC4623] Malis, A. and M. Townsley, "Pseudowire Emulation Edge-to-Edge (PWE3) Fragmentation and Reassembly", RFC 4623, August 2006.

- [RFC4720] Malis, A., Allan, D., and N. Del Regno, "Pseudowire Emulation Edge-to-Edge (PWE3) Frame Check Sequence Retention", RFC 4720, November 2006.
- [RFC4863] Martini, L. and G. Swallow, "Wildcard Pseudowire Type", RFC 4863, May 2007.
- [RFC5542] Nadeau, T., Ed., Zelig, D., Ed., and O. Nicklass, Ed., "Definitions of Textual Conventions for Pseudowires (PW) Management", RFC 5542, May 2009.

16.2. Informative References

- [CEPMIB] Zelig, D., Ed., Cohen, R., Ed., and T. Nadeau, Ed., "SONET/SDH Circuit Emulation Service Over Packet (CEP) Management Information Base (MIB) Using SMIV2", Work in Progress, January 2008.
- [RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", RFC 3410, December 2002.
- [RFC3916] Xiao, X., Ed., McPherson, D., Ed., and P. Pate, Ed., "Requirements for Pseudo-Wire Emulation Edge-to-Edge (PWE3)", RFC 3916, September 2004.
- [RFC3985] Bryant, S. and P. Pate, "Pseudo Wire Emulation Edge-to-Edge (PWE3) Architecture", RFC 3985, March 2005.
- [RFC5226] Narten, T. and H. Alvestrand, "Guidelines for Writing an IANA Considerations Section in RFCs", BCP 26, RFC 5226, May 2008.
- [RFC5602] Zelig, D., Ed., and T. Nadeau, Ed., "Pseudowire (PW) over MPLS PSN Management Information Base (MIB)", RFC 5602, July 2009.

Authors' Addresses

Thomas D. Nadeau (editor)
BT
BT Centre
81 Newgate Street
London EC1A 7AJ
United Kingdom

E-Mail: tom.nadeau@bt.com

David Zelig (editor)
Overssi Networks
1 Rishon Letzion St.
Petah Tikva
Israel

Phone: +972 77 3337 750
E-Mail: davidz@overssi.com